

List of takeCHARGE Qualifying HRV Models, Updated June, 2025

Brand	Model
Airflow	AIR100HEXF
Airflow	AIR155R
Airflow	AIR205-R
ALDES	H190TQG
ALDES	H190TRG
ALDES	H190TRGNOVO
ALDES	H280SRG
ALDES	H80HR
ALDES	H80HRNOVO
Broan	B150H75NT
Broan	B160H75RS
Broan	B160H75RT
Broan	B180H75NT
Broan	B230H75NT
Carrier	HRV200ECM
Carrier	HRV250ECM
Clean Comfort	VH30140RNC
Direct Air	PHRVR120-HE
Direct Air	PHRVR150-HE
Direct Air	PHRVR200-HE
Fantech	HERO 120H
Fantech	HERO 150H
Fantech	HERO200H
Fantech	HERO250H
Greentek	C3.14HRV
Greentek	Solace 1.2H
Greentek	Solace 1.5H
Greentek	Solace 2.0H
Healthy Climate	HRV3-195
Healthy Climate	HRV5-150
Healthy Climate	HRV5-200-TPD
Healthy Climate	HRV5270TPDECM
Healthy Climate	HRV6-HEX095-TPD
Lennox	HRV3300
Lifebreath	100ECM
Lifebreath	155MAX
Lifebreath	195DCS
Lifebreath	195ECM
Lifebreath	205MAX
Lifebreath	267MAX
Lifebreath	300DCS
Lifebreath	RNC155
Lifebreath	RNC205
Lifebreath	RNC5HEXTPF

Lifebreath	RNC6 HEX TPD
NEKTRA	NEKTRA 200
Nu-Air	EL1300
Nu-Air	ES150
Nu-Air	NU145
Reversomatic	RHRV-120PES
Reversomatic	RHRV-D100P ECM
Softaire	RHRV-130PES
vanEE	G2400H ECM
vanEE	G3000H ECM
vanEE	V160H75RS
vanEE	V160H75RT
vanEE	V180H75RT
vanEE	V230H75RT
Venmar	A160H75RS
Venmar	A160H75RT
Venmar	PRO 215 HRV
Venmar	X24HRV ECM
Venmar	X24HRV ECM N
Venmar	X30HRV ECM
Venmar	X30HRV ECM N

These models meet the takeCHARGE SRE and Fan Efficacy Minimum Requirements shown below

Minimum	Minimum
SRE at	SRE at
32°F (0°C)	-13°F (-25°C)
70%	63%